

LED_Linear family	IP65	Ik05	⊕ LEB		T _a 25	≥ 5	••		{{{_{_{_{_{_{_{_{_{_{_{_{_{_{_{_{_{_	
-------------------	------	------	----------	--	-------------------	------------	----	--	--------------------------------------	--

THE FAMILY OF SURFACE MOUNT LED LINEAR OPERATING AT 12W, 24 VDC INPUT. DELIVERING OUT STANDING PERFORMANCE OF 720LM.

Technical description

Luminaire for indoor architectural linear lighting and outdoor for landscape lighting. LED color temperature is 6000 kelvin (cool white). This is completely designed with polycarbonate, to gives a very pure and uniform pattern without glaring to have a good feeling. Uniform beam of light at 180° viewing angle. IP65. Total power: 12 w/m, 24 Constant voltage dimmable types driver can be used for dimming. Luminaries length can be changed by project submultiple 10 cm. Chromaticity tolerance (initial MacAdam: 3). Color rendering Ra>80.




Dimensions: 1000 x 34 x 41 mm

Total power: 12 w

Luminaire luminous flux: 600 lm Luminaire efficacy: 50 lm/w

Weight: 0.5 kg



Application

- Decorative
- Up light sign
- Landscape lighting

Correlated color temperature: 6000 kelvin Rated median useful life: 50000h L70 at 25°C

Luminaire input power: 12 w

Mounting and installation

Installation with stainless steel accessories (to be order separately).

Options:













