SEPEHR WID
12PL103006

AREND

LED_Linear family	IP44	IK05			T_a25					

THE FAMILY OF RECESSED MOUNT (CEILING & WALL) BACK LIGHT LED LINEAR OPERATING AT 36W 220-240 VAC INPUT. DELIVERING OUT STANDING PERFORMANCE OF 3600LM.

Technical description

Recessed linear system of wid dimensions, suitable both for decorative lighting and for grazing light, made of an aluminium anodized profile in matte white finish and a polycarbonate diffuser (or PMMA diffuser), which provide a continuos and homogeneous light line. Colour temperature is 6000 K (cool with) . Class I electrical and IP44 (IP54 just for option) with plug and play connector. Total power: 30 w/m (slave Luminaries for DALI control an option only) with LED converter. Colour rendering index: Ra > 80. Chromaticity tolerance between multiple luminaires of up to 3 MacAdam ellipses.



Dimensions: 1200 x 83 x 74 mm
Total power: 36 w
Luminaire luminous flux: 3600 lm
Luminaire efficacy: 100 lm/w
Weight: 1.7 kg





Application

- Office
- Bank
- Hospitality
- House

Correlated color temperature: 6000 kelvin
Rated median useful life: 50000h L70 at 25°C
Luminaire input power: 36 w

Mounting and installation

Recessed(ceiling and wall) using spring bracket. Cut-out diameters: 75 mm

Options: