


LED_Linear family	IP44	IK05	LED	⊕	T _a 25	📶	🔊	📶	🔌	
-------------------	------	------	-----	---	-------------------	---	---	---	---	--



THE FAMILY OF SURFACE MOUNT AND PENDANT LINEAR OPERATING AT 36W, 220-240 VAC INPUT. DELIVERING OUT STANDING PERFORMANCE OF 3600LM.

Technical description

Surface mount and pendant linear system for indoor general lighting. The lumenline is a linear system of LED luminaires which can be integrated in most ceiling types to provide a discreet flexible general lighting solution for commercial and institutional environments such as offices and class rooms. Luminaire for indoor architectural linear lighting with warm white LEDs (3000 kelvin). A LED Luminaires, flat direct LED with the top of the optical polystyrene diffuser (PC or PMMA an option) screen and extruded powder coating hard anodizing aluminum body, with aluminum end caps complete with silicone seals. Symmetric optic. Class I electrical and IP44 (IP54 just for option) with plug and play connector. Total power: 30 w/m, slave luminaire for DALI control (an option only) with LED converter. Chromaticity tolerance (initial MacAdam: 3). Color rendering Ra> 80.



Dimensions: 1200 x 89 x 50 mm
 Total power: 36 w
 Luminaries luminous flux: 3600lm
 Luminaire efficacy: 100 lm/w
 Weight: 3 kg



Application

- Corridors
- Office
- General
- Parking

Correlated color temperature: 3000 kelvin
 Rated median useful life: 50000h L70 at 25°C
 Luminaire input power: 36 w

Mounting and installation

Pendant and surface mount using the accessories to be ordered separately.

Options:

