

MAXIM WID
12PL503003



LED_Linear family	IP44	IK05			T _a 25					
-------------------	------	------	--	--	-------------------	--	--	--	--	--



THE FAMILY OF RECESSED, SURFACE MOUNT EDGE LIGHT LED LINEAR OPERATING AT 48W 220-240 VAC INPUT. DELIVERING OUT STANDING PERFORMANCE OF 3840LM.

Technical description

A recessed, surface, suspended LED luminaire with a slim 30mm profile. Electronic class I electrical, IP44 (IP54 only for option),IK05. Body: extruded powder coating (anodized option) aluminum. This is the very unique edge light LED panel with highly uniform distribution for special ceiling. Total power: 30 w/m, Diffuser: PMMA. Color rendering Ra>80, choice of color temperature: 6000 kelvin. Chromaticity tolerance initial MacAdam: 3. Suitable for ALUCOD ceiling.



Dimensions: 1600 x 200 x 30 mm
Total power: 48 w
Luminaries luminous flux: 3840 lm
Luminaries efficacy: 80 lm/w
Weight: 5 kg



Application

- ALUCOD ceiling
- Shopping mall
- Exhibition mall

Correlated color temperature: 6000 kelvin
Rated median useful life: 50000h L70 at 25°C
Luminaire input power: 48 w

Mounting and installation

Surface mounted (ceiling) using accessories to be ordered separately.

Options:

