

# MAXIM WID 12PL503005

**AREND**

LED_Linear family	IP44	IK05			$T_a 25$					
-------------------	------	------	--	--	----------	--	--	--	--	--



**THE FAMILY OF RECESSED, SURFACE MOUNT EDGE LIGHT LED LINEAR OPERATING AT 36W 220-240 VAC INPUT. DELIVERING OUT STANDING PERFORMANCE OF 2880LM.**

### Technical description

A recessed, surface, suspended LED luminaire with a slim 30mm profile. Electronic class I electrical, IP44 (IP54 only for option), IK05. Body: extruded powder coating (anodized option) aluminum. This is the very unique edge light LED panel with highly uniform distribution for special ceiling. Total power: 30 w/m, Diffuser: PMMA. Color rendering Ra>80, choice of color temperature: 4000 kelvin. Chromaticity tolerance initial MacAdam: 3. Suitable for ALUCOD ceiling.



Dimensions: 1200 x 200 x 30 mm  
 Total power: 36 w  
 Luminaries luminous flux: 2880 lm  
 Luminaries efficacy: 80 lm/w  
 Weight: 4 kg



### Application

- ALUCOD ceiling
- Shopping mall
- Exhibition mall

Correlated color temperature: 4000 kelvin  
 Rated median useful life: 50000h L70 at 25°C  
 Luminaire input power: 36 w

### Mounting and installation

Surface mounted (ceiling) using accessories to be ordered separately.

Options:

