

LED_Panel family	-	-		$T_a 25$					
------------------	---	---	--	----------	--	--	--	--	--



**THE FAMILY OF SUSPEND AND RECESSED BACK LIGHT LED PANEL OPERATING AT 30W, 220240 VAC INPUT. DELIVERING OUT STANDING PERFORMANCE OF 2730LM.**

**Technical description**

A suspended LED luminaire, flat direct LED with PS diffuser ceiling illumination. (IP42 just for options). For 600 x 600 mm square baffle ceiling. Total power: 30 w, slave luminaire for DALI control (an option only) with LED converter. Chromaticity tolerance (initial MacAdam: 3). Luminaire luminous flux: 2730 lm, Luminaire efficacy: 91 lm/w. Color rendering Ra > 80, color temperature 3000 kelvin.



Dimensions: 620 x 620 x 41.6 mm  
 Total power: 30 w  
 Luminaire luminous flux: 2730 lm  
 Luminaire efficacy: 91 lm/w  
 Weight: 2.5 kg



**Application**

- Office
- Bank
- Hospitality
- Education
- Showroom
- Fashion

Correlated color temperature: 3000 kelvin  
 Rated median useful life: 50000h L70 at 25°C  
 Luminaire input power: 30 w

**Mounting and installation**

Recessed installation with springs for plasterboard false ceilings.

Options:

