

LED_Panel family	-	Ik02		-	T _a 25						
------------------	---	------	--	---	-------------------	--	--	--	--	--	--



THE FAMILY OF RECESSED EDGE LIGHT PANEL OPERATING AT 24W, 220-240 VAC INPUT. DELIVERING OUT STANDING PERFORMANCE OF 2160LM.

Technical description

A ceiling recessed edge light LED luminaire with a slim 14 mm profile. Flat direct LED with polystyrene diffuser ceiling illumination. (IP42 just for options). Total power: 24 w, slave luminaire for DALI control (an option only) with LED converter Chromaticity tolerance (initial MacAdam: 3). Luminaries luminous flux: 2160 lm, Luminaries efficacy: 90 lm/w. Color rendering Ra > 80, color temperature 4000 kelvin.



Dimensions: 298 x 298 x 14 mm
 Total power: 24 w
 Luminaire luminous flux: 2160 lm
 Luminaire efficacy: 90 lm/w
 Weight: 1 kg



Application

- Office
- Bank
- Hospitality
- Education
- Showroom
- Fashion

Correlated color temperature: 4000 kelvin
 Rated median useful life: 50000h L70 at 25°C
 Luminaire input power: 24 w

Mounting and installation

Recessed in modular false ceilings suitable for panels can be use this family panel as suspend.

Options:

