

|                  |   |      |  |   |                   |  |  |  |  |  |
|------------------|---|------|--|---|-------------------|--|--|--|--|--|
| LED_Panel family | - | Ik02 |  | - | T <sub>a</sub> 25 |  |  |  |  |  |
|------------------|---|------|--|---|-------------------|--|--|--|--|--|

**THE FAMILY OF RECESSED EDGE LIGHT PANEL OPERATING AT 24W, 220-240 VAC INPUT. DELIVERING OUT STANDING PERFORMANCE OF 2160LM.**

**Technical description**

A ceiling recessed edge light LED luminaire with a slim 14 mm profile. Flat direct LED with polystyrene diffuser ceiling illumination. (IP42 just for options). Total power: 24 w, slave luminaire for DALI control (an option only) with LED converter Chromaticity tolerance (initial MacAdam: 3). Luminaries luminous flux: 2160 lm, Luminaries efficacy: 90 lm/w. Color rendering Ra > 80, color temperature 4000 kelvin.





Dimensions: 596 x 298 x 14 mm

Total power: 24 w

Luminaire luminous flux: 2160 lm

Luminaire efficacy: 90 lm/w

Weight: 1.5 kg



**Application**

- Office
- Bank
- Hospitality
- Education
- Showroom
- Fashion

Correlated color temperature: 4000 kelvin  
Rated median useful life: 50000h L70 at 25°C  
Luminaire input power: 24 w

**Mounting and installation**

Recessed in modular false ceilings suitable for panels can be use this family panel as suspend.

Options:

