

LED_Panel family	-	-		T _a 25					
------------------	---	---	--	-------------------	--	--	--	--	--



THE FAMILY OF CEILING RECESSED AND CEILING SURFACE PANEL OPERATING AT 120W, 220-240 VAC INPUT. DELIVERING OUT STANDING PERFORMANCE OF 13200LM.

Technical description

Luminaire was designed to be used white LEDs for illumination purposes can be surface mounted and ceiling suspended . Wide and uniform light distribution for decorative application. Down light luminaire with 120 w, color temperature (4000 kelvin) white LEDs for indoor applications. Robust luminaire housings made from aluminum. Diffuser is polycarbonate. All LEDs are within a three step MacAdam ellipse to ensure color consistency. Energy saving is up to 90% in comparison with traditional light sources.



Dimensions: Ø1130 x 135 mm
Total power: 120 w
Luminaries luminous flux: 13200 lm
Luminaire efficacy: 110 lm/w
Weight: 8 kg



Application

- Office
- Bank
- Hospitality
- Education
- Showroom
- Fashion

Correlated color temperature: 4000 kelvin
Rated median useful life: 50000h L70 at 25°C
Luminaire input power: 120 w

Mounting and installation

Surface and suspended mounting with special accessories to be ordered.

Options:

