

AMIN FLOOD LIGHT

12PI102001

AREND

| | | | | | | | | | | | |
|-----------------------|------|------|--|---|-------------------|--|--|--|--|--|--|
| LED_Industrial family | IP65 | IK05 | | - | T _a 25 | | | | | | |
|-----------------------|------|------|--|---|-------------------|--|--|--|--|--|--|



THE FAMILY OF FLOOD LIGHT AND INDUSTRIAL OPERATING AT 100W, 220-240 VAC INPUT. DELIVERING OUT STANDING PERFORMANCE OF 9000 LM.

Technical description

A modern and efficient LED pendant luminaire. Single point pendant LED high bay luminaire with medium beam optic (and adjustable beam angle in an option). Electronic, fixed output control gear, programmed for constant light output operation. Class I electrical, IP65, IK05. Housing material: extorted hard anodizing aluminum body. Lens: polycarbonate. Equipped with quick fit electrical connection. Color rendering Index: 80. color temperature: 3000 kelvin .



Dimensions: Ø200 x 352 mm
 Total power: 100 w
 Luminaries luminous flux: 9000 lm
 Luminaire efficacy: 90 lm/w
 Weight: 4.5 kg



Application

- General industry application
- High rack warehouse
- Decorative

Correlated color temperature: 3000 kelvin
 Rated median useful life: 50000h L70 at 25°C
 Luminaire input power: 100 w

Mounting and installation

Installation without removing lamp(s) and cover. Individual with hooks or bracket.

Options:

