AMIN HIGH BAY

AREND

12PI101004

LED_Industrial family	IP44	Ik05		-	T_a25				

THE FAMILY OF PENDANT, INDUSTRIAL HIGH BAY OPERATING AT 50W, 220-240 VAC INPUT. DELIVERING OUT STANDING PERFORMANCE OF 4500LM.

Technical descripion

A modern and efficient LED pendant luminaire. Single point pendant LED high bay luminaire with medium beam optic (and adjustable beam angle in an option). Electronic, fixed output control gear, programmed for constant light output operation. Class I electrical, IP44 (IP54 just an option), IK05. Housing material: extorted hard anodizing aluminum body. Lens: polycarbonate. Equipped with quick fit electrical connection. Color rendering Index: 80. color temperature: 4000 kelvin .

Dimensions: Ø200 x 352 mm
Total power: 50 w
Luminaire luminous flux: 4500 lm
Luminaire efficacy: 90 lm/w
Weight: 4.5 kg





Application

- General industry application
- High rack warehouse
- Decorative

Correlated color temperature: 4000 kelvin
Rated median useful life: 50000h L70 at 25°C
Luminaire input power: 50 w

Mounting and installation

Installation without removing lamp(s) and cover. Individual, with hooks or bracket.

Options: