NEPTUNE

12PI201002

AREND

LED_Industrial family	IP65	IK07									

THE FAMILY OF WALL MOUNT, CEILING SURFACE MOUNT AND CEILING PENDANT INDUSTRIAL LINEAR OPERATING AT 70W, 220-240 VAC INPUT. DELIVERING OUT STANDING PERFORMANCE OF 7700LM.

Technical descripion

Anodize aluminum body and polycarbonate cover material. Suitable for use in ambient temperatures ranging from-25ºC to 50ºC. Choice of color temperature: 4000 kelvin. Up to 50% energy savings compared with TL-D direct replacement for proof luminaires in terms of light performance, installation flexibility and length.IP65 [dust penetration protected, jet proof] wide beam angle light distribution. Diffuser with optical element ensures visual. Comfort ceiling-mounted bracket and suspension hooks included; installation can be made water proof by additional screw fixation of mounting brackets.

Dimensions: 1500 x 80 x 75 mm
Total power: 70 w
Luminaire luminous flux: 7700 lm
Luminaire efficacy: 110 lm/w
Weight: 2.7 kg





Application

- Parking garages
- Storeroom
- General lighting

Correlated color temperature: 4000 kelvin
Rated median useful life: 50000h L70 at 25°C
Luminaire input power: 70 w

Mounting and installation

Energy saving LED luminaire for wet and dusty rooms. Flexible mounting system for the easy replacement of traditional luminaires. Plug-and-play connector and mounting clips with adjustable position for the easy replacement of old fixtures.

Options: