12PS101004

LED _Spot & Under Water Family IP	P65	Ik08	⊕ ⊔в	-	T _a 25	<i>≱</i> 5	•	_Q	

THE FAMILY OF WALL WASHER (FLOOD) LINEAR OPERATING AT 20W, 220-240 VAC INPUT. DELIVERING OUT STANDING PERFORMANCE OF 2013LM.

Technical description

LED wall washer (Flood) luminaire with PMMA lens and extruded aluminum body. The top of the optical assembly is closed by a 3 mm thick transparent glass screen, which is fixed with silicone. Total power: 33 w/m , slave luminaire for DALI control (an option only) with LED converter. Luminaire luminous flux: 3300lm/m, Luminaire efficacy: 100 lm/w. Color rendering Ra > 80, color temperature 3000. Beam angel is 8°, 30° and 60°.




Dimensions: 610 x 64.3 x 33.5 mm

Total power: 20 w


Luminaire luminous flux: 2013 lm Luminaire efficacy: 100 lm/w

Weight: 1.6 kg



Application

- Facade lighting
- Flood light
- Decorative lighting
- Suitable where needs IP



Correlated color temperature: 3000 kelvin Rated median useful life: 50000h L70 at 25°C

Luminaire input power: 20 w

Mounting and installation

The luminaire can be installed bracket for wall, surface, or ceiling-mounting.

Opions:













