ROSHANA

12PS101008

LED _Spot & Under Water Family	IP65	Ik08		-	T_a25					

THE FAMILY OF WALL WASHER (FLOOD) LINEAR OPERATING AT 11W, 220-240 VAC INPUT. DELIVERING OUT STANDING PERFORMANCE OF 1089LM.

Technical description

LED wall washer (Flood) luminaire with PMMA lens and extruded aluminum body. The top of the optical assembly is closed by a 3 mm thick transparent glass screen, which is fixed with silicone. Total power: 33 w/m , slave luminaire for DALI control (an option only) with LED converter. Luminaire luminous flux: 3300lm/m, Luminaire efficacy: 100 lm/w. Color rendering Ra > 80, color temperature 4000 . Beam angel is 8° , 30° and 60°.

Dimensions: 330 x 64.3 x 33.5 mm
Total power: 11 w
Luminaire luminous flux: 1089 lm
Luminaire efficacy: 100 lm/w
Weight: 0.9 kg





Application

- Facade lighting
- Flood light
- Decorative lighting
- Suitable where needs IP

Correlated color temperature: 4000 kelvin
Rated median useful life: 50000h L70 at 25°C
Luminaire input power: 11 w

Mounting and installation

The luminaire can be installed bracket for wall, surface, or ceiling-mounting.

Opions: