LED _Spot & Under Water Family	IP65	IK08	⊕	_	T _a 25	5عر		Ω
			Lub	1	-			

THE FAMILY OF FLOODLIGHT. ARCHITECTURAL LED FLOOD LIGHT OPERATING AT 9 W DC INPUT DELIVERING OUT-STANDING PERFORMANCE OF 819LM.

Technical description


Luminaire was designed to be used as a flood light and up light using an integrated PMMA optical lens with several beam angle veriety. IP65, Ik08. Floodlight luminaire with 9 w, warm white and cool white LEDs for in- door and outdoor applications. color temperature is 3000 kelvin. Robust luminarie housings made of aluminum. All LEDs are within a three step MacAdam ellipse to ensure color consistency. (12v CV driver an option). (Brass bodies material is an option)



Dimensions: Ø 102 x 47 mm Total power: 9 w


Luminaire luminous flux: 819 lm Luminaire efficacy: 91 lm/w

Weight: 1.5 kg



Application

- Facade lighting
- Flood light
- Decorative lighting
- Suitable where needs IP



Correlated color temperature: 3000 kelvin Rated median useful life: 50000h L70 at 25°C Luminaire input power: 9 w

Mounting and installation

Simple installation with through wiring and integrated cable gland. Ground, wall installation using special bolt.

Opions:

















