

LED_Spot & Under Water Family	IP65	IK06	LED	T _a 25	5			
-------------------------------	------	------	-----	-------------------	---	--	--	--



THE FAMILY OF RECESSED, ARCHITECTURAL LED UP LIGHT TRIM OPERATING AT 9W DC INPUT DELIVERING OUT STANDING PERFORMANCE OF 819LM.

Technical description

Luminaire was designed to be used as an up light using an integrated PMMA optical lens with several beam angles. IP65, IK06. Up light luminaire with 9 w, color temperature: 4000 kelvin, LEDs for indoor and outdoor applications. Robust luminaire's housings made of aluminum. All LEDs are within a three step MacAdam ellipse to ensure color consistency. (12v CV driver an option). (Brass bodies material is an option)



Dimensions: Ø119 x 47 mm
 Total power: 9 w
 Luminaire luminous flux: 819 lm
 Luminaire efficacy: 91 lm/w
 Weight: 1.5 kg



Application

- Facade lighting
- Flood light
- Decorative lighting
- Suitable where needs IP

Correlated color temperature: 4000 kelvin
 Rated median useful life: 50000h L70 at 25°C
 Luminaire input power: 9 W

Mounting and installation

Suitable for indoor and outdoor, simple installation with through wiring and integrated cable gland. Cut-out diameters: "LEI MID-UP-T": 100 mm

Options:

