

LED_Spot & Under Water Family	IP65	IK06	LED	T <sub>a</sub> 25	5				
-------------------------------	------	------	-----	-------------------	---	--	--	--	--



**THE FAMILY OF RECESSED, ARCHITECTURAL LED UP LIGHT TRIM OPERATING AT 9W DC INPUT DELIVERING OUT STANDING PERFORMANCE OF 819LM.**

### Technical description

Luminaire was designed to be used as an up light using an integrated PMMA optical lens with several beam angles. IP65, IK06. Up light luminaire with 9 w, color temperature: 6000 kelvin, LEDs for indoor and outdoor applications. Robust luminaire's housings made of aluminum. All LEDs are within a three step MacAdam ellipse to ensure color consistency. (12v CV driver an option). (Brass bodies material is an option)



Dimensions: Ø119 x 47 mm  
 Total power: 9 w  
 Luminaire luminous flux: 819 lm  
 Luminaire efficacy: 91 lm/w  
 Weight: 1.5 kg



### Application

- Facade lighting
- Flood light
- Decorative lighting
- Suitable where needs IP

Correlated color temperature: 6000 kelvin  
 Rated median useful life: 50000h L70 at 25°C  
 Luminaire input power: 9 W

### Mounting and installation

Suitable for indoor and outdoor, simple installation with through wiring and integrated cable gland. Cut-out diameters: "LEI MID-UP-T": 100 mm

Options:

