

LEI MINI DL-T 12PS206001

AREND

LED_Spot & Under Water family	IP54	IK06		-	T _a 25					
-------------------------------	------	------	--	---	-------------------	--	--	--	--	--



THE FAMILY OF RECESSED, ARCHITECTURAL LED DOWN LIGHTS TRIM OPERATING AT 3.5W DC INPUT DELIVERING OUT STANDING PERFORMANCE OF 318LM.

Technical description

Luminaire was designed to be used as a downlight using an integrated PMMA optical lens with several beam angle variety. IP54 (IP65 for- option), IK06. Down light luminaire with 3.5w (1w to 5w for options) color temperature: 3000 kelvin, LEDs for indoor and outdoor applications. Beam angel is 15', 30', 45' or 60' extruded DC, CC or CV driver. Robust luminaries housing made of aluminum. All LEDs are within three step MacAdam ellipse to ensure color consistency. (12v CV driver an-option)
body material is aluminum. (Steel and brass body is option)



Dimensions: Ø55 x 58 mm
Total power: 3.5 w
Luminaire luminous flux: 318 lm
Luminaire efficacy: 91 lm/w
Weight: 0.35 kg



Application

- Facade lighting
- Down lighting
- Decorative lighting
- Suitable where needs IP

Correlated color temperature: 3000 kelvin
Rated median useful life: 50000h L70 at 25°C
Luminaire input power: 3.5 w

Mounting and installation

Suitable for indoor and outdoor recessed, ceiling mounting, cut out dimension: Ø32mm. LEI can be installed directly from the box into a wide range of ceiling types including the thickness of 1mm - 40mm. Remote driver makes installation and maintenance quick and easy.

Options:

