LEI MINI FL-TL 12PS203001

LED Spot & Under Water Family	IP65	IK08	€	T _a 25	5عر	•	0	
,			uto				M	

THE FAMILY OF ARCHITECTURAL LED FLOOD LIGHTS TRIMLESS OPERATING AT 3.5W DC INPUT DELIVERING OUT STANDING PERFORMANCE OF 318LM.

Technical description


Luminaire was designed to be use as a mini flood light an integrated PMMA optical lens, with several beam angle variety (15, 30, 45 or 60). IP65, Ik08. Flood light luminaire with 3.5w Correlated color temperature: 3000 kelvin, LEDs for indoor and outdoor applications. External DC,CC or CV driver ro- bust luminaries housings made of aluminum. All LEDs are within a three step MacAdam ellipse to ensure color consistency. (12v CV driver an option) Body material is hard anodized aluminum. (steel and brass body heads material is an option)



Dimensions: Ø 33 x 68 mm Total power: 3.5 w


Luminaire luminous flux: 318 lm Luminaire efficacy: 91 lm/w

Weight: 0.3 kg



Application

- Facade lighting
- flood lighting
- Decorative lighting
- Suitable where needs IP



Correlated color temperature: 3000 kelvin Rated median useful life: 50000h L70 at 25°C

Luminaire input power: 3.5 w

Mounting and installation

For outdoor applications, fixed with bolt.s IP

Opions:

















