

12PS205003

AREND

LED_Spot & Under Water family	lþ65	IK08			T ₈ 25					
-------------------------------	------	------	---	--	-------------------	---	---	---	---	--

THE FAMILY OF RECESSED, ARCHITECTURAL LED TRIM UP LIGHTS OPERATING AT 3.5W DC INPUT DELIVERING OUT- STANDING PERFORMANCE OF 318LM.

Technical description

Luminaire was designed to be used as an up light with several beam angle variety using an integrated PMMA optical lens, with several beam angle variety (15, 30, 45 or 60), IP65, IK08. Up light luminaire with 3.5w (1w to 5w for options), color temperature: 6000 kelvin LEDs for indoor and outdoor applications with DC, CC or CV driver. Robust luminaire housings made of aluminum. All LEDs are within three step MacAdam ellipse to ensure color consistency. (12v CV driver an option)

Body material is hard anodized aluminum. (Heads material of steel and brass is an option)





Dimensions: Ø55 x 58 mm

Total power: 3.5 w

Luminaire luminous flux: 318 lm

Luminaire efficacy: 91 lm/w

Weight: 0.35 kg



Application

- Facade lighting
- Decorative lighting
- Suitable where needs IP

Correlated color temperature: 6000 kelvin
Rated median useful life: 50000h L70 at 25°
Luminaire input power: 3.5 W

Mounting and installation

Recessed in pavement and floor with outer casing. For outdoor applications, 30cm drainage gravel or any equivalent drainage system should be used beneath the housing to ensure water evacuation.

Options:

