LEI MINI UP-T

12PS204003

AREND

LED _Spot & Under Water Family	IP65	IK08		-	T_a25					

THE FAMILY OF ARCHITECTURAL LED UP LIGHT TRIMLESS AT 3.5W DC INPUT DELIVERING OUT STANDING PERFORMANCE OF 318LM.

Technical description

Luminaire was designed to be used trimless up light be recessed using an integrated PMMA optical lens , with several beam angle variety (15°, 30°,45° or 60°) IP65, IK08. Up light luminaire with 3.5 w, color temperature: 6000 kelvin, LEDs for indoor and outdoor applications external DC, CC or CV driver. Robust luminarie housings made of Aluminum. All LEDs are within three step MacAdam ellipse to ensure color consistency. (12v CV driver an option) Body material is hard anodize aluminum. (Steel and brass body is option)

Dimensions: Ø 33 x 58 mm
Total power: 3.5 w
Luminaire luminous flux: 318 lm
Luminaire efficacy: 91 lm/w
Weight: 0.35kg





Application

- Facade lighting
- Up lighting
- Decorative lighting
- Suitable where needs IP

Correlated color temperature: 6000 kelvin
Rated median useful life: 50000h L70 at 25°C
Luminaire input power: 3.5 w

Mounting and installation

Recessed in pavement and floor with outer casing. For outdoor applications, 30cm drainage gravel or any equivalent drainage system should be used beneath the housing to ensure water evacuation. The recessed box can be embedded in asphalt with good drainage once the temperature of the asphalt is approximately 80°C.

Opions: