

12PD101001

| | | | | | | | | | | |
|-----------------------|------|------|--|---|-------------------|--|--|--|--|--|
| LED_Decorative family | IP42 | Ik05 | | - | T _a 25 | | | | | |
|-----------------------|------|------|--|---|-------------------|--|--|--|--|--|

The FAMILY OF SURFACE MOUNT AND PENDANT LED LINEAR DECORATIVE LIGHTS OPERATING AT 19.2W, 220-240 VAC INPUT DELIVERING OUTSTANDING PERFORMANCE OF 576LM.

Technical description

Luminaire for indoor architectural linear lighting (LED color temperature is 3000 kelvin). A surface LED luminaire, flat direct LED with 20 mm x 70 mm opaque PMMA diffuser and body: extruded anodize aluminum (powder coating an option). IP42 (IP44 only for option). Total power: 12 w/m, Slave luminaire for DALI control (an option only) with LED converter. Chromaticity tolerance (initial MacAdam: 3). Color rendering Ra>80. For special ceiling. (24v DC driver an-option)





Dimensions: 1600 x 106 x 20 mm

Total power: 19.2 w

Luminaire luminous flux: 576 lm

Luminaire efficacy: 30 lm/w

Weight: 3.6 kg



Application

- ALUCOD ceiling
- Shopping mall
- Exhibition hall

Correlated color temperature: 3000 kelvin
 Rated median useful life: 50000h L70 at 25°C
 Luminaire input power: 19.2 w

Mounting and installation

Surface (ceiling) and pendant mounted using accessories to be ordered separately.

Options:

