LIOSA NARROW
12PD101005

LED_Decoraitve family	IP42	Ik05		-	T_a25					

The FAMILY OF SURFACE MOUNT AND PENDANT LED LINEAR DECORATIVE LIGHTS OPERATING AT 14.5W, 220-240 VAC INPUT DELIVERING OUTSTANDING PERFORMANCE OF 430LM.

Technical description

Luminaire for indoor architectural linear lighting (LED color temperature is 4000 kelvin). A surface LED luminaire, flat direct LED with 20 mm x 70 mm opaque PMMA diffuser and body: extruded anodize aluminum (powder coating an option). IP42 (IP44 only for option). Total power: 12 w/m, Slave luminaire for DALI control (an op- tion only) with LED converter. Chromaticity tolerance (initial MacAdam: 3). Color rendering Ra> 80. For special ceiling. (24v DC driver an-option)

Dimensions: 1200 x 106 x 20 mm
Total power: 14.5 w
Luminaire luminous flux: 430 lm
Luminaire efficacy: 30 lm/w
Weight: 2.4 kg





Application

- ALUCOD ceiling
- Shopping mall
- Exhibition hall

Correlated color temperature: 4000 kelvin
Rated median useful life: 50000h L70 at 25°C
Luminaire input power: 14.5 w

Mounting and installation

Surface (ceiling) and pendant mounted using accessories to be ordered separately.

Options: