LIOSA NARROW
12PD101009

AREND

LED_Decoraitve family	IP42	Ik05	LED	-	T_a25	5				

The FAMILY OF SURFACE MOUNT AND PENDANT LED LINEAR DECORATIVE LIGHTS OPERATING AT 7.2W, 220-240 VAC INPUT DELIVERING OUTSTANDING PERFORMANCE OF 216LM.

Technical description

Luminaire for indoor architectural linear lighting (LED color temperature is 6000 kelvin). A surface LED luminaire, flat direct LED with 20 mm x 70 mm opaque PMMA diffuser and body: extruded anodize aluminum (powder coating an option). IP42 (IP44 only for option). Total power: 12 w/m, Slave luminaire for DALI control (an op- tion only) with LED converter. Chromaticity tolerance (initial MacAdam: 3). Color rendering Ra> 80. For special ceiling. (24v DC driver an-option)

Dimensions: 800 x 106 x 20 mm
Total power: 7.2 w
Luminaire luminous flux: 216 lm
Luminaire efficacy: 30 lm/w
Weight: 1.2 kg





Application

- ALUCOD ceiling
- Shopping mall
- Exhibition hall

Correlated color temperature: 6000 kelvin
Rated median useful life: 50000h L70 at 25°C
Luminaire input power: 7.2 w

Mounting and installation

Surface (ceiling) and pendant mounted using accessories to be ordered separately.

Options: