

LIOSA MID

12PD102001

AREND

LED_Decoraive family	IP44	IK06	LED	25	5					
----------------------	------	------	-----	----	---	--	--	--	--	--



THE FAMILY OF SURFACE MOUNT AND PENDANT LED LINEAR DECORATIVE OPERATING AT 32W, 220-240 VAC INPUT. DELIVERING OUT STANDING PERFORMANCE OF 896LM.

Technical description

Luminaire for indoor architectural linear lighting, LED color temperature is 3000 kelvin. A surface LED luminaire, flat direct light distribution with 20 mm opaque PMMA diffuser and body: extruded anodize aluminum (powder coating an option). Class I electrical, IP44 (IP54 only for option). Total power: 20 w/m, slave luminaire for DALI control (an option only) with LED converter. Chromaticity tolerance (initial MacAdam: 3). Color rendering Ra>80.



Dimensions: 1600 x 40 x 100 mm
 Total power: 32 w
 Luminaire luminous flux: 896 lm
 Luminaire efficacy: 28 lm/w
 Weight: 3.4 kg



Application

- ALUCOD ceiling
- Shopping mall
- Exhibition hall
- Food court

Correlated color temperature: 3000 kelvin
 Rated median useful life: 50000h L70 at 25°C
 Luminaire input power: 32 w

Mounting and installation

Surface mounted (ceiling) using accessories to be ordered separately.

Options:

