LIOSA MID

12PD102004

AREND

LED_Decoraive family	IP44	IK06			T_a25					

THE FAMILY OF SURFACE MOUNT AND PENDANT LED LINEAR DECORATIVE OPERATING AT 24W, 220-240 VAC INPUT. DELIVERING OUT STANDING PERFORMANCE OF 672LM.

Technical description

Luminaire for indoor architectural linear lighting, LED color temperature is 3000 kelvin. A surface LED luminaire, flat direct light distribution with 20 mm opaque PMMA diffuser and body: extruded anodize aluminum (powder coating an option). Class I electrical, IP44 (IP54 only for option). Total power: 20 w/m, slave luminaire for DALI control (an option only) with LED converter. Chromaticity tolerance (initial MacAdam: 3). Color rendering Ra> 80.

Dimensions: 1200 x 40 x 100 mm
Total power: 24 w
Luminaire luminous flux: 672 lm
Luminaire efficacy: 28 lm/w
Weight: 2.61 kg





Application

- ALUCOD ceiling
- Shopping mall
- Exhibition hall
- Food court

Correlated color temperature: 3000 kelvin
Rated median useful life: 50000h L70 at 25°C
Luminaire input power: 24 w

Mounting and installation

Surface mounted (ceiling) using accessories to be ordered separately.

Options: