# 12PD102005

LED_Decoraive family	IP44	IK06	⊕	T <sub>a</sub> 25	5عر	•	~ ^
			_		_		

## THE FAMILY OF SURFACE MOUNT AND PENDANT LED LINEAR DECORATIVE OPERATING AT 24W, 220-240 VAC INPUT. DELIVERING OUT STANDING PERFORMANCE OF 672LM.

### **Technical description**

Luminaire for indoor architectural linear lighting, LED color temperature is 4000 kelvin. A surface LED luminaire, flat direct light distribution with 20 mm opaque PMMA diffuser and body: extruded anodize aluminum (powder coating an option). Class I electrical, IP44 (IP54 only for option). Total power: 20 w/m, slave luminaire for DALI control (an option only) with LED converter. Chromaticity tolerance (initial MacAdam: 3). Color rendering Ra>




Dimensions: 1200 x 40 x 100 mm

Total power: 24 w


Luminaire luminous flux: 672 lm Luminaire efficacy: 28 lm/w

Weight: 2.61 kg



## **Application**

- ALUCOD ceiling
- Shopping mall
- Exhibition hall
- Food court



Correlated color temperature: 4000 kelvin Rated median useful life: 50000h L70 at 25°C

Luminaire input power: 24 w

#### Mounting and installation

Surface mounted (ceiling) using accessories to be ordered separately.

Options:











