

AREVIK EYELIT 12PD408002

AREND




THE FAMILY OF ARCHITECTURAL PENDANT SINGLE LED LIGHTS OPERATING AT 9W 220AC INPUT DELIVERING OUT- STANDING PERFORMANCE OF 540LM.

Technical description

Luminaire was designed to be used as a decorative pendant LED light to illumination for home and hotel area with sets of luxury atmosphere. Body material is the raw brass without any extra coating. Opaque PMMA optic lens with very uniform and anti-glaring distribution. The sleek and classic design. In addition, you can change the color temperature of the light from a calming warm white to an invigorating day light /neutral tone. The lamp contains no tungsten, mercury or other toxic materials or fragile glass parts. Its unique design makes for a great conversation piece while enhancing any kind of traditional, urban, contemporary, or minimalist decor. Available in oxidized gold , nickel or copper with a high glass ,matte or brushed finished.



Dimensions: $\varnothing 40 \times 476$ mm
Total power: 9 w
Luminaire luminous flux: 540 lm
Luminaire efficacy: 60 lm/w
Weight: 1 kg



Application

- Hotel
- Office
- Home

Correlated color temperature: 4000 kelvin
Rated median useful life: 50000h L70 at 25°C
Luminaire input power: 9 W

Mounting and installation

Pendant with special bracket which is fixed by bolt.

Options:

