

LED_Downlight family	IP54	lk03		-	-					
----------------------	------	------	--	---	---	--	--	--	--	--



THE FAMILY OF CEILING SURFACE MOUNTED AND PENDANT LED LIGHT OPERATING AT 12 W 220-240 VAC INPUT. DELIVERING OUT STANDING PERFORMANCE OF 1080LM.

Technical description

Recessed Luminaire designed to use white LEDs for in be recessed , down light.downlight luminaire with 12w , 3000k (warm white) LEDs for in door applications. robust luminaire housings made from aluminum.high efficienecy LEDs tested to LM 80 standards, 40000hrs lifetime with lumen maintenance atL70. All LEDs are within a 2 step MacAdam ellipse to ensure color consistency.



Dimensions: Ø185 mm x 35 mm
 Total power: 12 w
 Luminaire luminous flux: 1080 lm
 Luminaire efficacy: 90 lm/w
 Weight: 0.7 kg



Application

- Hotel
- Restuaran
- Retail
- Home

Correlated color temperature: 3000 kelvin
 Rated median useful life: 40000h L70 at 25°C
 Luminaire input power: 12 w

Mounting and installation

Suitable for indoor recessed, ceiling mounting, cut out dimension: 153mm. Simple installation with fitting springs.

Options:

