

MAGNETAR DOT LINEAR
12PLM102001

AREND

LED_Low voltage family	IP20	IK05	LED	⊕	T _a 25	5	🔊		🔌	
------------------------	------	------	-----	---	-------------------	---	---	--	---	--

THE FAMILY OF RECESSED TRIMLESS MAGNETIC TRACK LIGHT LINEAR LED OPERATING AT 28.8W, 48 VDC INPUT. DELIVERING OUT STANDING PERFORMANCE OF 2800LM.



Technical description

Magnetic track DOT linear luminaire with several optic element makes an impact with their streamlined design and generate base lighting that illuminates objects and rooms especially evenly.

Body material is extruded aluminium and diffuser is UGR<19 and beam angle is 42°. Quick installation system on the track using magnets. Class I electrical, IP20 (IP44 only for option). Total power: 24 w/m. (DALI control an option only). LED color temperature is 3000 kelvin (warm white). Chromaticity tolerance (initial MacAdam: 3). Color rendering Ra>80.



Dimensions: 1200 x 40 x 47 mm
 Total power: 28.8 w
 Luminaire luminous flux: 2800 lm
 Luminaire efficacy: 100 lm/w
 Weight: 1.2 kg



Correlated color temperature: 3000 kelvin
 Rated median useful life: 50000h L70 at 25°C
 Luminaire input power: 28.8 w

Application

- Decorative
- Art gallery
- Hotel
- Office
- House

Mounting and installation

Quick installation system on the track using magnets.

Options:

