

RAHA 35

THE FAMILY OF SURFACE MOUNT DOWNLIGHT





LED_Downlight family		LED -	T _a 25	<i>y</i> 5		A	~]
----------------------	--	-------	-------------------	------------	--	---	---	--	---

THE FAMILY OF SURFACE MOUNT DOWNLIGHT OPERATING AT 3 W, 220-240 VAC INPUT. DELIVERING OUT STANDING PERFORMANCE OF 330LM.

Technical description


A surface mount decorative LED luminaire, to be used as a dark light dome where needs emotional and sense luxury, Body: Extruded Anodised Aluminium (powder coating an option), Reflector made of pure anodised aluminium. Total power: 3 w, slave luminaire for DALI control (an option only) with LED converter. Chromaticity tolerance (initial MacAdam: 3). Color rendering Ra > 80, color temperature 3000°-6000K.

This product can be producted in height 200, 300 and 400 mm.




Application

- Decorative
- Accent light



Correlated color temperature: 3000 - 6000 kelvin Rated median useful life: 50000h L70 at 25°C Luminaire

input power: 3 w



Dimensions: Ø35 x 200 mm

Total power: 3 w

Luminaire luminous flux: 330 lm Luminaire efficacy: 110 lm/w

Weight: 0.5 kg

Mounting and installation

Surface mount the luminaire from the ceiling with special accessories is in the luminarie case.

Options:

Body:

















