

# **SEPEHR PLUS**

THE FAMILY OF RECESSED MOUNT BACK LIGHT LED LINEAR



## **SEPEHR PLUS**



LED_Linear family	IP44	IK05	<b>⊕</b>	<b>(</b>	T <sub>a</sub> 25	<i>y</i> 5	••		<u> </u>	
-------------------	------	------	----------	----------	-------------------	------------	----	--	----------	--

THE FAMILY OF RECESSED MOUNT (CEILING & WALL) BACK LIGHT LED LINEAR OPERATING AT45W/M 220-240 VACINPUT. DELIVERING OUT STANDING PERFORMANCE OF 4500LM/M.

#### **Technical description**


Recessed linear system of large dimensions, suitable for general light, ps diffuser, which provide a continuos and homogeneous light line. Colour temperature is 3000-6000 K. Class I electrical and IP44 (IP54 just for option), with plug and play connector. Total power: 45 w/m (slave Luminaries for DALI control an option only with LED converter). Colour rendering index:Ra>80. Chromaticity tolerance between multiple luminaires of up to 3 MacAdam ellipses.

product can be producted in 60, 120 , 160, 180 and 220 mm.




#### **Application**

- Office
- Bank
- Hospitality
- House



Correlated color temperature: 3000 - 6000 kelvin Rated median useful life: 50000h L70 at 25°C Luminaire

input power: 45 w



Dimensions: 1000 x 115 x 82 mm

Total power: 45 w

Luminaire luminous flux: 4500 lm Luminaire efficacy: 100 lm/w

Weight: 1.6 kg

### Mounting and installation

Recessed(ceiling and wall) using spring bracket. Cut-out diameters: 95 mm

Options:















