

# **MAGNETAR ANGLE DOT**

THE FAMILY OF MAGNETIC PENDANT LIGHT LED 48VDC INPUT.



## MAGNETAR ANGLE DOT



LED\_Low voltage family IP43 IK05 3 T<sub>a</sub>25 15 (1)

## THE FAMILY OF LIGHT ANGLE DOT LINEAR LED OPERATING AT 10W, 48 VDC INPUT. DELIVERING **OUT STANDING PERFORMANCE OF 1100LM.**


#### **Technical description**

Mangetic track RotateDot linear luminaire with several optic element makes an impact with their streamlined design and generate base lighting that illuminates objects and rooms especially evenly. This light can be rotated 350 degrees. Body material is extruded aluminium and diffuser is UGR<19 and beam angle is 42°. Quick installation system on the track using magnets. Class I electrical, IP43 (IP44 only for option). Total power: 10 w. (DALI control an option only). LED color temperature is 3000-6000 kelvin (warm white). Chromaticity tolerance (initial MacAdam: 3). Color rendering Ra>80.




### **Application**

- Decorative
- Art gallery
- Hotel
- Office
- House



Correlated color temperature: 3000-6000 kelvin Rated median useful life: 50000h L70 at 25°C

Luminaire input power: 10 w



Dimensions: 270 x 35 x 140mm

Total power: 10 w

Luminaire luminous flux: 1100 lm Luminaire efficacy: 110 lm/w

Weight: 0.7 kg

#### Mounting and installation

Quick installation system on the track using magnets. that embeded in luminair.

Options:



















