

MAGNETAR DOT LINEAR

THE FAMILY OF LINEAR LED 48VDC INPUT.



MAGNETAR DOT LINEAR



LED_Low voltage family	IP43	IK05			T _a 25	۶5						
------------------------	------	------	--	--	-------------------	----	--	--	--	--	--	--

THE FAMILY OF MAGNETAR DOT LINEAR LED OPERATING AT 24W, 48 VDC INPUT. DELIVERING **OUT STANDING PERFORMANCE OF 2200LM..**

Technical description

Mangetic track DOT linear luminaire with several optic element makes an impact with their streamlined design and generate base lighting that illuminates objects and rooms especially evenly.


Body material is extruded aluminium and diffuser is UGR<19 and beam angle is 42°. Quick installation system on the track using magnets. Class I electrical, Ip43 (IP44 only for option). Total power:24w. (DALI control an option only). LED color temperature is 3000 kelvin (1000-4000). Chromaticity tolerance (initial MacAdam: 3). Color rendering Ra>80.

This. product can be producted in 270, 530 and 770




Application

- Decorative
- Art gallery
- Hotel
- Office
- House



Correlated color temperature: 3000-6000 kelvin Rated median useful life: 50000h L70 at 25°C

Luminaire input power: 24 w



Dimensions: 530 x 35 x 70 mm

Total power:24 w

Luminaire luminous flux: 2200 lm Luminaire efficacy: 110 lm/w

Weight: 0.6 kg

Mounting and installation

Quick installation system on the magnetar track using magnets.that embeded in luminair.

Options:

Body:













