

MAGNETAR ROTATE DOT

THE FAMILY OF MAGNETAR ROTATE DOT LINEAR LIGHT LED 48VDC INPUT.



MAGNETAR ROTATE DOT



₩ LED_Low voltage family IP43 IK05 T_a25 15 \triangle 3 1

THE FAMILY OF MAGNETIC LINIEAR DOT TRACK LIGHT, ROTATE DOT LED OPERATING AT 10W, 48 VDC INPUT, DELIVERING OUT STANDING PERFORMANCE OF 1100LM.


Technical description

Mangetic track RotateDot linear luminaire with several optic element makes an impact with their streamlined design and generate base lighting that illuminates objects and rooms especially evenly. This light can be rotated 350 degrees. Body material is extruded aluminium and diffuser is UGR<19 and beam angle is 42°. Quick installation system on the track using magnets. Class I electrical, IP43 (IP44 only for option). Total power: 10 w. (DALI control an option only). LED color temperature is 3000-6000 kelvin (warm white). Chromaticity tolerance (initial MacAdam: 3). Color rendering Ra>80.




Application

- Decorative
- Art gallery
- Hotel
- Office
- House



Correlated color temperature: 3000-6000 kelvin Rated median useful life: 50000h L70 at 25°C

Luminaire input power: 10 w



Dimensions: 270 x 35 x 128 mm

Total power: 10 w

Luminaire luminous flux: 1100 lm Luminaire efficacy: 110 lm/w

Weight: 0.6 kg

Mounting and installation

Quick installation system on the track using magnets. that embeded in luminair.

Options:















